



Field and Brush Mower SPECIFICATIONS

Tow-Behind Models



13.3 FPT PREMIER-44

16.5 HP PRO-44

20.0 HP PRO XL-44

CUT			
CUTTING WIDTH	44"	44"	44"
CUTTING CAPACITY	4'-high grass; 6'-high weeds & brush; 2.5"-thick saplings	4'-high grass; 8'-high weeds & brush; 3"-thick saplings	6'-high grass; 8'-high weeds & brush; 3"-thick saplings
NUMBER OF BLADES	2	2	2
CUTTING HEIGHT	4" to 7.5"	4" to 7.5"	4" to 7.5"
BLADE ENGAGEMENT	On Machine	Remote Control	Remote Control
ENGINE			
TYPE	DR® OHV	Briggs & Stratton Professional OHV	Briggs & Stratton Professional OHV
STARTING	Electric-Starting	Electric-Starting	Electric-Starting
CYLINDER	One (cast-iron sleeve)	One (cast-iron sleeve)	Two (cast-iron sleeve)
DISPLACEMENT	340cc	500cc	650 cc
AIR FILTER	Paper + Foam	Dual-Element	Dual-Element
FUEL SYSTEM			
LUBRICATION	Splash	Full pressure pump with oil filter	Full pressure pump with oil filter
FUEL CAPACITY	0.92 gallon	2.5 gallons with fuel pump and fuel filter	2.5 gallons with fuel pump and fuel filter
TIRES			
FRONT	11 x 4-5, Flat Free	11 x 4-5, Flat Free	11 x 4-5, Flat Free
REAR	13 x 5-6, Lugged (with tube)	13 x 5-6, Lugged (with tube)	13 x 5-6, Lugged (with tube)
GENERAL			
OFFSET POSITIONS	5	5	5
HITCH STYLE	Pin	Pin	Pin
DIMENSIONS			
L X W X H	146" L x 46.5" W x 30.5" T	146" L x 46.5" W x 29.5" T	146" L x 46.5" W x 32.5" T
WEIGHT	413 lbs.	448 lbs.	460 lbs.
WARRANTIES			
MACHINE WARRANTY	2 years residential; 90 days commercial	2 years residential; 90 days commercial	2 years residential; 90 days commercial
ENGINE WARRANTY	2 years residential; 1 year commercial	2 years residential; 1 year commercial	2 years residential; 1 year commercial