



Field and Finish Mower

SPECIFICATIONS

Tow-Behind Models



**13.3 FPT
MOW PRO-44**

**14.5 HP
MOW PRO-60**

CUT		
CUTTING WIDTH	44"	60"
CUTTING CAPACITY	1'-high grass	1'-high grass
NUMBER OF BLADES	2	3
BLADE TYPE	Air-Tipped	Air-Tipped
CUTTING HEIGHT	1.5 - 5.5"	1.5 - 5.5"
ENGINE		
TYPE	DR® OHV	Briggs & Stratton Professional OHV
STARTING	Manual-Starting	Electric-Starting
CYLINDER	One (cast-iron sleeve)	One (cast-iron sleeve)
DISPLACEMENT	340cc	481 cc
AIR FILTER	Paper + Foam	Cartridge
FUEL SYSTEM		
LUBRICATION	Splash	Full pressure pump with oil filter
FUEL CAPACITY	3.5 L (.92 gal)	2.5 gallons with fuel pump and fuel filter
TIRES		
TREAD	Turf Tread	Turf Tread
DIMENSIONS	11" X 4"	11" X 4"
GENERAL		
OFFSET POSITIONS	5	5
HITCH STYLE	Pin	Pin
DIMENSIONS		
L X W X H	132"L x 60"W x 29"H	132"L x 75"W x 26"H
WEIGHT	270 lbs.	320 lbs.
WARRANTIES		
MACHINE WARRANTY	2 years residential; 90 days commercial	2 years residential; 90 days commercial
ENGINE WARRANTY	2 years residential; 1 year commercial	2 years residential; 1 year commercial