



Log Splitters SPECIFICATIONS Hydraulic Models



**22-TON
HORIZONTAL/
VERTICAL**



**28-TON
HORIZONTAL/
VERTICAL**



**34-TON
HORIZONTAL/
VERTICAL**



**22-TON
3-PT HITCH
HORIZONTAL/
VERTICAL**



**34-TON
3-PT HITCH
HORIZONTAL/
VERTICAL**

**5-TON
ELECTRIC**

	22-TON HORIZONTAL/ VERTICAL	28-TON HORIZONTAL/ VERTICAL	34-TON HORIZONTAL/ VERTICAL	22-TON 3-PT HITCH HORIZONTAL/ VERTICAL	34-TON 3-PT HITCH HORIZONTAL/ VERTICAL	5-TON ELECTRIC
Engine	DR®	DR®	Briggs & Stratton	Category 1 Tractor (18hp min)	Category 1 Tractor (18hp min)	N/A
Foot Pounds Torque	9.59	9.59	14.5	N/A	N/A	N/A
Valve	OHV	OHV	OHV	N/A	N/A	N/A
Cylinders	1	1	1	N/A	N/A	N/A
Air Filter	Dual	Dual	Dual	N/A	N/A	N/A
Pump	2 stage, 8.8 / 2.1 GPM	2 stage, 8.8/2.1GPM	2 stage, 13 / 3.0 GPM	N/A	N/A	N/A
Splitting force	22 ton	28 ton	34 ton	Up to 22 tons (Tractor dependent)	Up to 34 tons (Tractor dependent)	5 Tons
Splitting length	25"	25"	25"	25"	25"	20"
Splitting diameter	30"	30"	30"	30"	30"	10"
Cylinder bore	4"	4.5"	5"	4"	5"	N/A
Cylinder stroke	23.65"	23.65"	23.65"	24"	24"	18.5"
Cycle feed time (seconds)	14.5	17	16	14-26 Tractor Dependent	14-26 Tractor Dependent	18
Hydraulic max pressure	3400 psi	3450 psi	3500 psi	3400 psi	3400 psi	2700 psi
Cradle	Included	Included	Included	Included	Included	Included
Ball Coupler	2"	2"	2"	N/A	N/A	N/A
Road Tow Speed (mph)	45	45	45	N/A	N/A	N/A
Machine Dim's (L x W x H)	83.6" x 40.6" x 35.4"	83.6" x 40.6" x 35.4"	83.6" x 40.6" x 35.4"	72" x 23" x 43"	72" x 23" x 43"	39.5" x 13.5" x 20"
Net Weight (lbs)	474	511	549	440	488	104