



# Log Splitters SPECIFICATIONS

## RapidFire™ Flywheel Models



**K10 RAPIDFIRE  
ELECTRIC BENCHTOP**



**K22 RAPIDFIRE  
PREMIER**



**K28 RAPIDFIRE PRO**

**K34 RAPIDFIRE PRO-XL**

ENGINE/MOTOR	1060 Watts	3.5 FPT DR® Manual-Start 115 Volt, 6.7 Amp, 360 Watt Electric	7.5 FPT Briggs & Stratton OHV Manual-Start	9.5 FPT Briggs & Stratton OHV Manual, Electric-Start
OUTSPLITS	10-ton	22-ton	28-ton	34-ton
MAX. LOG LENGTH	16 in.	18 in.	24 in.	24 in.
MAX. LOG DIAMETER	12 in.	30 in.	30 in.	30 in.
AVERAGE CYCLE TIME	1 second	2.5 seconds	3 seconds	3 seconds
WEIGHT	132 lbs.	Gas: 275 lbs. — Elect: 285 lbs.	395 lbs.	435 lbs.
SIZE	49"L X 12"W X 25"H	79"L X 25"W X 46"H	100.9"L X 46.8"W X 48.3"H	100.9"L X 46.8"W X 48.3"H
BED HEIGHT	9.25"	24"	27"	27"
WEDGE HEIGHT	5"	6.2"	6.2"	6.2"
WEDGE WIDTH	.75"	.78"	.78"	.78"
FLYWHEEL WEIGHT	12.5 lbs. each (25 lbs. total)	55 lbs.	55 lbs. each (110 lbs. total)	75 lbs. each (150 lbs. total)
FLYWHEEL DIAMETER	12"	18.25"	18.25"	18.25"
FLYWHEEL MAX RPM	490 RPM	400 RPM	400 RPM	400 RPM
STEEL TABLE	N/A	Standard (Heavy-Duty Optional)	Heavy-Duty Standard	Heavy-Duty Standard
TIRES	6"	11"	16"	16"